

# Technical data sheet

## 90° Quick pipe bend, pure white

Item number: 2154064



Fitting for plastic electrical installation pipes to create 90° bends. Suitable for Quick pipe pipes or corrugated pipes. Toolless closing and opening. Can be used in a temperature range of -25 to +60 °C.



**PP** Polypropylene

### Master data

|                                   |                         |
|-----------------------------------|-------------------------|
| Item number                       | 2154064                 |
| Type                              | 3000 BMS M20 RW         |
| Description 1                     | 90° Quick pipe bend     |
| Manufacturer                      | OBO                     |
| Dimension                         | M20                     |
| Colour                            | Pure white; RAL 9010    |
| Material                          | Polypropylene           |
| Smallest sales unit               | 5                       |
| Unit of quantity                  | Piece                   |
| Weight                            | 1.103 kg                |
| Weight unit                       | kg/100 pc.              |
| CO Footprint (GWP) Cradle-to-Gate | 0,0825 kg COe / 1 Piece |


# Technical data sheet

90° Quick pipe bend, pure white

Item number: 2154064



## Dimensions



|              |         |
|--------------|---------|
| Dimension B  | 26.3 mm |
| Dimension d  | 20 mm   |
| Dimension L  | 83.2 mm |
| Dimension L1 | 35 mm   |
| Dimension R  | 22 mm   |

## Technical data

|                                   |           |
|-----------------------------------|-----------|
| Version for                       | Connector |
| Flexible                          | no        |
| Halogen-free                      | yes       |
| With inspection opening and lid   | no        |
| With sleeve                       | no        |
| Brushed surface                   | no        |
| Polished surface                  | no        |
| Permitted temperature range, max. | 60 °C     |
| Permitted temperature range, min. | 0 °C      |
| Angle of the bend                 | 90 °      |
| Two-part                          | yes       |