

Technical data sheet

Drop-in anchor E

Item no. 3492910



Drop-in anchor for single fixings of non-load-bearing systems in non-cracked concrete as well as for multiple fixings in cracked and non-cracked concrete.
Tested to fire protection standards, fire resistance class R 120 according to European Technical Approval ETA-02/0020 (option 7) and European Technical Approval ETA-05/0116.
Mounting with marking and setting tool.



St	Steel
G	Electrogalvanised

Master data

Item no.	3492910
Type	E M 8x40
Description 1	Drop-in anchor E
Dimension	M8x40
Material	Steel
Material symbol	St
Surface	Electrogalvanised
Surface to DIN	EN ISO 19598 / EN ISO 4042
Surface symbol	G
Smallest sales unit (VG)	100 Piece
Weight	1,49 kg/100 pc.

Technical data

	Length	40,00 mm
	Dimension L	40,00 mm
	Version	Lightning strike
	Fastening unit	Other
	Drill hole depth	40,00 mm
	Drill hole diameter	10,00 mm
	Screw-in depth min.-max.	9,00 - 20,00 mm
	Thread	M8
	Thread metric	8
	Self-drilling	<input type="checkbox"/>
	Permitted load range, tension zone	2,00 kN
	Approvals available	<input checked="" type="checkbox"/>