

# Technical data sheet

PDP cover, 2-pin, with OS, 5 V

Item number: 5080422



Upper part, plug-in data cable protection, type 1+2/D1+C2, for use in measurement, control and regulation technology

- Protection device for multi-wire systems
- Frequency range up to 100 MHz
- Low construction width of 17.5 mm
- With visual signalling and option of remote signalling


Application: Universal lightning and surge voltage protection for data transmission devices in MCR technology.



## Master data

|                     |                                |
|---------------------|--------------------------------|
| Item number         | 5080422                        |
| Description 1       | Pluggable data line protection |
| Description 2       | plug-in arrester 2-pole        |
| Manufacturer        | OBO                            |
| Dimension           | 5V                             |
| Smallest sales unit | 1                              |
| Unit of quantity    | Piece                          |
| Weight              | 2.6 kg                         |
| Weight unit         | kg/100 pc.                     |

## Dimensions



|        |         |
|--------|---------|
| Length | 51 mm   |
| Width  | 17.5 mm |
| Height | 46 mm   |


# Technical data sheet

PDP cover, 2-pin, with OS, 5 V

Item number: 5080422



## Technical data



|                                            |                             |
|--------------------------------------------|-----------------------------|
| Connection cross-section, flexible, max.   | 1.5 mm <sup>2</sup>         |
| Connection cross-section, flexible, min.   | 0.14 mm <sup>2</sup>        |
| Connection cross-section, multi-wire, max. | 2.5 mm <sup>2</sup>         |
| Connection cross-section, multi-wire, min. | 0.14 mm <sup>2</sup>        |
| Connection cross-section, rigid, max.      | 2.5 mm <sup>2</sup>         |
| Connection cross-section, rigid, min.      | 0.14 mm <sup>2</sup>        |
| Insertion loss                             | ≤3 dB                       |
| Earthing via:                              | Connection cable / DIN rail |
| Total discharge current (10/350)           | 2,5 kA                      |
| Total discharge current (8/20)             | 20 kA                       |
| Cut-off frequency                          | 100 MHz                     |
| Maximum continuous voltage AC              | 4.2 V                       |
| Maximum continuous voltage DC              | 6 V                         |
| Lightning impulse current                  | 2.5 kA                      |
| Capacity (wire-wire)                       | ≤30 pF                      |
| Capacity (wire-earth)                      | ≤30 pF                      |
| Kategorie                                  | Type 1+2 / D1+C2            |
| Lightning protection zone LPZ              | 0→2                         |
| Lengthwise resistance                      | 1.2 ± 5%                    |
| Mounting of input / output                 | Screw terminals             |
| Mounting type                              | DIN rail 35 mm              |
| Nominal discharge current (8/20 μs)        | 10 kA                       |
| Nominal load current AC                    | 0.425 A                     |
| Nominal load current DC                    | 0.6 A                       |
| Total impulse durability into C2 (8/20)    | 20 kA                       |
| Testing standard                           | IEC 61643-21                |
| Shielding connection available             | yes                         |
| Screening                                  | Direct                      |
| Protection rating                          | IP20                        |
| Series resistance per wire                 | 1,2 Ω ± 5%                  |
| Signalling on device                       | None                        |
| SPD to EN 61643-11                         | Type 1+2                    |
| SPD to IEC 61643-1                         | Class I+II                  |
| SPD to IEC 61643-21                        | Class I+II / D1+C2          |
| Plug-in system                             | Terminal                    |
| Impulse durability wire-wire               | 10 kV / 5 kA                |
| Impulse durability wire-earth              | 10 kV / 5 kA                |
| Permitted temperature range, max.          | 80 °C                       |
| Permitted temperature range, min.          | -40 °C                      |