Technical data sheet

Height-adjustable cassette with cord outlet, RKSR, stainless steel

Item number: 7409270





Height-adjustable cassette of nominal size R7 with cord outlet for installation of accessories in dry-care floors for indoor use.

Height-adjustable cassette for cord outlet, 3-compartment. 2 APMT2 cover plates and 1 APMT5 cover plate can be installed. For the installation of 2 UT3 universal supports and one UT4 universal support for 7 individual installation devices with support ring/support clamp or 10 Modul 45 devices.





Stainless steel, grade 354/1

Master data

| Item number | 7409270 |
|---------------------|------------------------------|
| Туре | RKS2 R7 V25 |
| Description 1 | Round cassette |
| Description 2 | with cord outlet |
| Manufacturer | OBO |
| Dimension | Ø275mm |
| Material | Stainless steel, grade 354/1 |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 340 kg |
| Weight unit | kg/100 pc. |
| | • |


Technical data sheet

Height-adjustable cassette with cord outlet, RKSR, stainless steel


Item number: 7409270



Dimensions



| Length | 274 mm |
|--------|--------|
| Width | 274 mm |



Technical data

| Number of installable devices | 10 |
|--|-------------------------|
| Number of mounting boxes | 3 |
| Number of cable outlets | 1 |
| Version for | Round |
| Cable outlet version | Swivellable cord outlet |
| Floor care | Dry |
| Decouplable | no |
| Floor height, max. | 155 mm |
| Floor height, min. | 110 mm |
| Suitable for raised floor installation | yes |
| Suitable for cavity floor installation | yes |
| Suitable for underfloor box | 350 |
| Device support to accept mounting boxes | yes |
| Nominal size for device installation units | R7 |
| Height-adjustment range, max. | 155 mm |
| Height-adjustment range, min. | 110 mm |
| Protection rating (IP) when used | IP20 |
| Protection rating (IP) when unused | IP40 |
| Protection rating IK code | IK10 |
| Heavy-duty version | no |
| Installation system type | UT3 / UT4 |
| Vertical load, large area | to 5,000 N |
| Vertical load, small area | to 3,000 N |
| Approvals | VDE |