

# Technical data sheet

## Clamp clip, single, FT plastic pressure trough

Item number: 1175408



Suitable for all C profile rails with slot width 18 mm and 22 mm.

Polypropylene pressure trough, halogen-free, colour light grey RAL 7035.



**St** Steel

**FT** Hot-dip galvanised

### Master data

Item number	1175408
Type	2056U 40 FT
Description 1	Clamp clip
Manufacturer	OBO
Dimension	34-40mm
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	100
Unit of quantity	Piece
Weight	8.1 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,1451 kg COe / 1 Piece


# Technical data sheet

## Clamp clip, single, FT plastic pressure trough

Item number: 1175408



### Dimensions



Dimension A	20 mm
Dimension B	45 mm
Dimension C	34 mm
Dimension G (mm)	M8
Dimension H	73 mm
Dimension L	37.5 mm
Dimension t	2 mm
Dimension x	5.5 mm

### Technical data

Number of cables/pipes	1
for 1 cable H	73 mm
for 1 cable L	37.5
for 2 cable H	115 mm
for 2 cable L	44.5 mm
for 3 cable H	157 mm
for 3 cable L	44.5 mm
For pipe diameter, max.	40 mm
For pipe diameter, min.	40 mm
for rail with slot width (with interval), max.	22 mm
for rail with slot width (with interval), min.	18 mm
Halogen-free	yes
Max. Tightening torque	5 Nm
With plastic trough	yes
With metal trough	no
Mounting type	Profile rail
Impact-resistant	no
Clamping range D, max.	40 mm
Clamping range D, min.	34 mm
Surface addition	hot galvanised
Material addition	Steel
With counter-trough	no
Material of trough	Plastic
Material quality of trough	Polypropylene