

Technical data sheet

Stainless steel pipe, V2A

Item number: 2046721



Electrical installation pipe without threaded ends to EN 61386-1 for mechanical protection of cables. With burr-free inner wall. Corrosion protection class 4 (high). Classification according to DIN EN 61386-1: 555711404010



A2 Stainless steel

2B Bright, treated

Master data

| | |
|------------------------------------|--------------------------|
| Item number | 2046721 |
| Type | S20W A2 |
| Description 1 | Stainless steel pipe |
| Description 2 | without thread |
| Manufacturer | OBO |
| Dimension | Ø20, 3000mm |
| Material | Stainless steel 1.4301 |
| Surface | Bright, treated |
| Surface standard | |
| Smallest sales unit | 30 |
| Unit of quantity | Metre |
| Weight | 46.9 kg |
| Weight unit | kg/100 m |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,7708 kg CO2e / 1 Meter |



Technical data sheet

Stainless steel pipe, V2A

Item number: 2046721



Dimensions



| | |
|------------------|----------|
| Length | 3,000 mm |
| Dimension D | 20 mm |
| Dimension L | 3,000 mm |
| Dimension m (mm) | M20 |
| Dimension t | 1 mm |

Technical data sheet

Stainless steel pipe, V2A

Item number: 2046721



Technical data

| | |
|--|-------------------------|
| Surface-mounted | yes |
| Pipe version | Rigid without thread |
| Concrete installation | yes |
| Bending behaviour | rigid |
| Pressure resistance | Very heavy (4,000 N) |
| Use temperature, max. | + 400 °C |
| Use temperature, min. | - 45 °C |
| Cavity wall installation | yes |
| Installation on wood | yes |
| Installation in the earth | yes |
| Installation outdoors | yes |
| Classification code | 55571 |
| Machines and system installation | yes |
| With sleeve | no |
| Brushed surface | yes |
| Polished surface | no |
| Impact resistance | Very heavy (6.8/300 mm) |
| Permitted temperature range, max. | 400 °C |
| Permitted temperature range, min. | -45 °C |
| Underfloor installation (bitumen, hot asphalt) | yes |
| Underfloor installation (screed) | yes |
| Concealed | yes |