# Technical data sheet

### 45° bend 60 FT

**Item number: 6036136** 



45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.



# CER

St

Steel



Hot-dip galvanised

### Master data

Item number	6036136
Туре	RB 45 630 FT
Description 1	45° bend
Description 2	for cable tray, horizontal
Manufacturer	OBO
Dimension	60x300
Colour	zinc
Material	Steel
Surface	Hot-dip galvanised
Surface standard	DIN EN ISO 1461
Smallest sales unit	1
Unit of quantity	Piece
Weight	107.3 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	3,0617 kg CO2e / 1 Piece

# **Technical data sheet**

## 45° bend 60 FT

**Item number: 6036136** 



# Dimensions 296 379

Width	300 mm
Height	60 mm
Plate thickness	0.8 mm
Dimension B	300 mm

### Technical data

Bend (angle)	45°
Connector version	Integrated connector
Type	Bend, rigid
Maintain electrical functions	yes
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	14 St.
Rail thickness	1.25 mm