


Technical data sheet

Wiring trunking, type LK4H N 100100

Item number: 6132576



Halogen-free wiring duct, incl. cover and base perforation, for horizontal and vertical routing of electrical cables in the switchgear cabinet. With double-sided adhesive tape on the duct base as a mounting aid. Designed as a metric duct. Retainers are broken out without tools. Special lengths on request. Tested to DIN EN 50085-2-3. Base and cover in set.



Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

| | |
|---------------------|--|
| Item number | 6132576 |
| Type | LK4H N 100100 |
| Description 1 | Slotted cable trunking system |
| Description 2 | halogen-free |
| Manufacturer | OBO |
| Colour | Light grey; RAL 7035 |
| Material | Polycarbonate/Acrylnitrile-butadiene-styrene |
| Smallest sales unit | 2 |
| Unit of quantity | Metre |
| Weight | 90 kg |
| Weight unit | kg/100 m |


Technical data sheet

Wiring trunking, type LK4H N 100100

Item number: 6132576



Dimensions



| | |
|--------|----------|
| Length | 2,000 mm |
| Width | 100 mm |
| Height | 100 mm |

Technical data

| | |
|-----------------------------------|-----------------------|
| Side wall version | Slotted |
| Fastening type | Base perforation |
| Flexible | no |
| Halogen-free | yes |
| Creepage current-resistant | yes |
| With cover | yes |
| Usable cross-section | 90.12 cm ² |
| Slot spacing | 5.5 mm |
| Slot width | 4.5 mm |
| Self-extinguishing | yes |
| Permitted temperature range, max. | 90 °C |
| Permitted temperature range, min. | -25 °C |