Technical data sheet

LCIS 60 cable ladder, 3 m C30 FS

Item number: 6209614





Cable ladder with a 60 mm side height with welded C30 profile rungs which are open in an upwards direction. Rolled side rail for reinforcement and as edge protection. Fastening to the bracket takes place using hold-down clamps, type LKS 40. The slot dimension of the rung is 16.5 mm and the appropriate clamp clip is type BS-H....

Magnetic shield insulation without cover 10 dB, with cover 15 dB.



St

Steel

FS

Strip galvanized

Master data

Item number	6209614
Туре	LCIS 640 3 FS
Description 1	Cable ladder
Description 2	perforated rung, welded
Manufacturer	OBO
Dimension	60x400x3000
Colour	zinc
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	3
Unit of quantity	Metre
Weight	310.34 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to- Gate	7,5721 kg CO2e / 1 Meter


Technical data sheet

LCIS 60 cable ladder, 3 m C30 FS





Dimensions




Length	3,000 mm
Width	400 mm
Height	60 mm
Dimension B	400 mm
Rung slot dimension	17.00


Technical data

Version of the rungs	Profile perforated
Side rail version	Flat profile
Fastening of rung	Welded
Mounting system fastening type	Floor Ceiling Wall
Maintain electrical functions	no
Usable cross-section	160 cm ²
Usable cross-section	16000 mm²
Rustproof steel, pickled	no
Side perforation	yes
Rung distance	300 mm
Wide-span version	no
Rail thickness	1.5 mm

Loads

Insertable support spacings, min.	1.5 m
Insertable support spacings, max.	4 m
Support spacing 1.5 m	3.3 kN/m
Support spacing 2.0 m	2 kN/m
Support spacing 2.5 m	1.3 kN/m
Support spacing 3.0 m	1 kN/m
Support spacing 3.5 m	0.78 kN/m
Support spacing 4.0 m	0.4 kN/m





- Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- Rail bend in mm at permitted kN/m
- Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width