Technical data sheet

UDHOME-ONE floor socket, without floor covering recess, BS socket, stainless steel

Item number: 7368306





Square floor socket for use in dry-care systems and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 75 mm, the height-adjustment range +30 mm. Frame and cover made of stainless steel and visible in the floor covering. Cover with decorative plate. The delivery includes a switched BS socket.

CEUK

A2

Stainless steel

Master data


| Item number | 7368306 | |
|--|---------------------------|--|
| Туре | UDHOME-ONE V BS | |
| Description 1 | Floor socket | |
| Description 2 | with BS socket, decor lid | |
| Manufacturer | OBO | |
| Dimension | 140x140x75 | |
| Material | Stainless steel | |
| Smallest sales unit | 1 | |
| Unit of quantity | Piece | |
| Weight | 199 kg | |
| Weight unit | kg/100 pc. | |
| CO2 Footprint (GWP) Cradle-to- Gate | 11,3384 kg CO2e / 1 Piece | |


Technical data sheet

UDHOME-ONE floor socket, without floor covering recess, BS socket, stainless steel



Item number: 7368306





Technical data

| Number of sockets according to the British standard | 1 |
|---|-------------------------|
| Cable outlet version | Swivellable cord outlet |
| Equipment | Single BS socket |
| Floor covering protection frame | no |
| Floor care | Dry |
| Cover version | Decorative plate |
| Seal installation option | no |
| Application when used | 6.101.1 Dry floor care |
| Application when unused | 6.101.1 Dry floor care |
| Floor height, max. | 105 mm |
| Floor height, min. | 75 mm |
| Suitable for raised floor installation | yes |
| Suitable for screed-flush closed underfloor ducts | no |
| Suitable for screed-covered underfloor ducts | no |
| Suitable for cavity floor installation | yes |
| Suitable for wet care | no |
| Suitable for underfloor ducts | no |
| Device support to accept mounting boxes | no |
| With floor covering recess | no |
| Protection rating (IP) when used | IP20 |
| Protection rating (IP) when unused | IP40 |
| Protection rating IK code | IK10 |
| Heavy-duty version | no |
| Vertical load, large area | to 15,000 N |
| | |

Technical data sheet

UDHOME-ONE floor socket, without floor covering recess, BS socket, stainless steel Item number: 7368306



| Technical data | | |
|----------------|---------------------------|------------|
| | Vertical load, small area | to 3,000 N |
| | Opening mechanism | Handle |