Technical data sheet

UDHOME2 floor socket, with brush outlet, without floor covering recess, unequipped, stainless steel ltem number: 7368352





Square floor socket for use in dry-care cavity and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 100 mm, the height-adjustment range 35 mm. Frame and cover made of stainless steel and visible in the floor covering. Cover with decorative plate and brush bar for cable routing. Empty housing for up to 2 Modul 45® devices in the mounting support and 2 data sockets in the optional data technology support.



A2

Stainless steel

2B

Bright, treated

Master data


Item number	7368352
Туре	UDHOME2 BN
Description 1	Floor socket
Description 2	unequipped, with brush outlet
Manufacturer	OBO
Dimension	140x140x110
Material	Stainless steel
Surface	Bright, treated
Surface standard	
Smallest sales unit	1
Unit of quantity	Piece
Weight	220 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to- Gate	12,24 kg CO2e / 1 Piece

Technical data sheet

UDHOME2 floor socket, with brush outlet, without floor covering recess, unequipped, stainless steel Item number: 7368352



Dimensions			
	Length	140 mm	
	Width	140 mm	
	Height	100 mm	
	Dimension h	100 mm	



Technical data

Number of installable devices	2
No. of entries	8
Number of mounting boxes	0
Number of SCHUKO sockets	0
Number of sockets according to the British standard	0
Version for	Square
Cable outlet version	Brush bar
Equipment	Empty housing
Floor covering protection frame	no
Floor care	Dry
Cover version	Decorative plate
Seal installation option	no
Application when used	6.101.1 Dry floor care
Application when unused	6.101.1 Dry floor care
Screed height, max.	135 mm
Screed height, min.	100 mm
Floor height, max.	135 mm
Floor height, min.	100 mm
Suitable for outdoor use	no
Suitable for raised floor installation	yes
Suitable for screed-flush closed underfloor ducts	no
Suitable for screed-covered underfloor ducts	no
Suitable for cavity floor installation	yes
Suitable for wet care	no
Suitable for underfloor ducts	no
Device support to accept mounting boxes	no
Length of external dimensions	140 mm
Length of installation dimensions	144 mm
With floor covering recess	no

Technical data sheet

UDHOME2 floor socket, with brush outlet, without floor covering recess, unequipped, stainless steel Item number: 7368352



Technical data	
Nominal size for device on units	ee installati- 2
Height-adjustment ran	nge, max. 135 mm
Height-adjustment ran	nge, min. 100 mm
Protection rating (IP)	when used IP20
Protection rating (IP) sed	when unu-
Protection rating IK co	ode IK10
Heavy-duty version	no
Vertical load, large are	ea to 15,000 N
Vertical load, small ar	ea to 3,000 N
Approvals	VDE