

Technical data sheet

Connection shackle, conductive, for EÜK-2

Item number: 7400996



Connection shackle for mounting screed-covered underfloor installation ducts.
The connection shackle snaps in to the duct sidewalls.
The electrical conductivity is ensured via the snap-in connection.



- St** Steel
- FS** Strip galvanized

Master data

Item number	7400996
Type	VL 350-2
Description 1	Connection shackle
Description 2	conductive for EÜK-2
Manufacturer	OBO
Dimension	423x75x28,2
Material	Steel
Surface	Strip galvanized
Surface standard	DIN EN 10346
Smallest sales unit	1
Unit of quantity	Piece
Weight	54.58 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	1,2825 kg CO2e / 1 Piece


Technical data sheet

Connection shackle, conductive, for EÜK-2

Item number: 7400996



Dimensions



Length	423 mm
Width	75 mm
Dimension a	350 mm



Technical data

Version for	Strap
Floor plate	yes
Seal installation option	no
Suitable for expansion joint	yes
Trunking width, min.	350 mm
Trunking height, max.	58 mm
Duct height, min.	28 mm
With equipotential bonding	yes
Removable cover	yes