

Technical data sheet

Height-adjustable cassette for tube body, RKFN, stainless steel

Item number: 7408960



Height-adjustable cassette for tube bodies of nominal size 4 for the installation of devices in duct systems, raised and cavity floors in interior dry or wet-care floors. Protection class: IP X5.

For the installation of two UT3 universal supports for four single devices with support ring/support clamp or six Modul 45® devices. 2 APMT2 cover plates can be installed. The tube body is not contained in the scope of delivery.



A2 Stainless steel

Master data

Item number	7408960
Type	RKFN3 4 VS 20
Description 1	Square cassette
Description 2	Lid for tube body
Manufacturer	OBO
Dimension	199x199x100
Material	Stainless steel
Smallest sales unit	1
Unit of quantity	Piece
Weight	260 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	15,8564 kg CO2e / 1 Piece


Technical data sheet

Height-adjustable cassette for tube body, RKFN, stainless steel


Item number: 7408960



Dimensions



Length	199 mm
Width	199 mm
Height	105 mm
Dimension h	105 mm



Technical data

Number of installable devices	6
Number of cable outlets	1
Number of universal supports	2 x UT3
Version for	Square
Cable outlet version	Lowerable tube body
Floor cut-out / Mounting opening	201x201
Floor care	Wet
Decouplable	no
Floor height, max.	150 mm
Floor height, min.	105 mm
Suitable for raised floor installation	yes
Suitable for cavity floor installation	yes
Suitable for underfloor box	250/350
Device support to accept mounting boxes	no
Length of installation dimensions	201 mm
Nominal size for device installation units	4
Height-adjustment range, max.	150 mm
Height-adjustment range, min.	105 mm
Standard	EN 50085-2-2
Protection rating (IP) when used	IP20
Protection rating (IP) when unused	IP55
Protection rating IK code	IK10
Heavy-duty version	no
Installation system type	UT3
Vertical load, large area	to 5,000 N
Vertical load, small area	to 3,000 N
Approvals	VDE
Floor covering thickness	20 mm