Technical data sheet

FireBox T100ED with plug-in seal and internal fastening

Item no. 7205530





Halogen-free junction box with pre-mounted, soft plug-in seals, approved for the maintenance of electrical functionality according to DIN 4102 Part 12.

 $\label{eq:maintenance} \mbox{ Maintenance of electrical functionality classes E30 to E90.}$

Colour: Pastel orange.

Including pre-mounted connection unit made of high temperature-resistant special ceramic and labelled protective conductor terminal. Supplied with 2 MMS 6x50 fire protection screw ties for

Nominal cross-section of power cable: Max. 6 mm², data cable with wire Ø 0.8 mm. Maximum of three 1.5 mm² rigid copper cables per terminal.

High protection rating IP66, impact resistance class IK08.

Details on the cable types and manufacturers can be found in the general construction test certificate of the material testing institute NRW, Erwitte.

Number of terminals including protective conductor terminal. Internal clearance: 136x102x57 mm.










Polypropylene

Master data

Item no.	7205530
Туре	T 100 ED 6-5
Description 1	Junction box
Description 2	for function maintenance
Dimension	150x116x67
Colour	Pastel orange
RAL number	2003
Material	Polypropylene
Material symbol	PP
Smallest sales unit (VG)	1 Piece
Weight	34,00 kg/100 pc.

Technical data





Length	150,00 mm
Width	116,00 mm
Height	67,00 mm
Clear internal dimensions	136x102x57 mm
Dimension LxWxH	150x116x67 mm
Dimension	150x116x67 mm
Expandable	
No. of entries	10
Number of terminals	5
Type of housing penetration	Cuttable stepped membrane
Measured insulation voltage Vi	690,00 V
Equipment	Terminal
Cover	Not transparent
Cover fastening	Screwed
Entries	8x M25 2x M32
Entry from rear	
Explosion-tested version	
Shape	Rectangular
Function maintenance (ETIM)	E 90
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Halogen-free	
With screening	
With cover	
Nominal cross section	6.00 mm ²

Technical data sheet

FireBox T100ED with plug-in seal and internal fastening Item no. 7205530

