

Technical data sheet

Cable gland with locknut as a set

Item no. 7205663



Robust cap nut cable gland with metric connecting thread to IEC 423, including pre-mounted locknut.

For high tightness requirements. Strain relief, torsion protection and tightness over the whole clamping area. Sealing ring made of polychloroprene/acrylonitrile butadiene rubber. Moulded shaped sealing lip on intermediate support, no connection thread sealing ring required.

VDE-tested according to DIN EN 50262, protection rating IP68 at 5 bar for 1 hr.

For maintenance of electrical function according to DIN 4102 Part 12 in connection with the closed junction boxes of the FireBox T series.


Colour: Pastel orange.

PA Polyamide

Master data

Item no.	7205663
Type	V-TEC VM25+ OR
Description 1	Cable gland
Description 2	with locknut
Dimension	M25
Colour	Pastel orange
RAL number	2003
Material	Polyamide
Material symbol	PA
Smallest sales unit (VG)	10 Piece
Weight	1,71 kg/100 pc.

Technical data



Dimension E	32,00 mm
Dimension E1	32,00 mm
Dimension E2	36,00 mm
Dimension G	M25 x 1,5 mm
Dimension L min.	26,00 mm
Dimension L max.	35,00 mm
Dimension L1	10,00 mm
Dimension L2	6,00 mm
Dimension L3	6,50 mm
WAF	29,00 mm
SW 1	29,00 mm
SW 2	32,00 mm
Bend protection	<input type="checkbox"/>
Sealing range D	9,00 - 17,00 mm
Flat cable threaded connection	<input type="checkbox"/>
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Thread	M25 x 1,5
Thread type	Metric
Thread length	10,00 mm
Thread increase	1,50 mm

Technical data sheet

Cable gland with locknut as a set

Item no. 7205663



Technical data

Fibre-glass reinforced	<input type="checkbox"/>
Halogen-free	<input checked="" type="checkbox"/>
Installation torque	5,00 Nm
Multiple sealing insert	<input type="checkbox"/>
With locknut	<input checked="" type="checkbox"/>
Impact-resistant	<input type="checkbox"/>
Protection rating	IP68
Splittable gland	<input type="checkbox"/>
max. permitted ambient temperature	-20,00 - 65,00 °C
Strain relief option	<input checked="" type="checkbox"/>