Technical data sheet

Magic 60 fitting connector

Item no. 6065722





Magic straight connector for direct and screwless joining of Magic fittings with a side height of

The straight connector is equipped with four brackets and can also be used for the direct connection with a cut cable tray with only two brackets mounted to one side. To join a cut cable tray with a fitting, an additional Magic straight connector set is needed.

The fitting connector is compatible with cable tray types MKSM, MKSMU, SKSM and SKSMU.







St


Steel

Strip galvanised zinc/aluminium, Double Dip

Master data

Item no.	6065722
Туре	FVM 660 DD
Description 1	Straight connector
Description 2	with quick connector
Dimension	60x600
Material	Steel
Material symbol	St
Surface	Strip galvanised zinc/aluminium, Double Dip
Surface to DIN	DIN EN 10346
Surface symbol	DD
Smallest sales unit (VG)	1 Piece
Weight	94,60 kg/100 pc.

Technical data



Length	135,00 mm
Width	600,00 mm
	·
Height	60,00 mm
Side height	60,00 mm
Side height	2,00 in
Dimension B	600,00 mm
Version	Straight connector
Suitable for cable tray system height	60,00 mm
Suitable for cable tray	\square
Suitable for mesh cable tray	
Suitable for cable ladder	
Suitable for maintaining electrical function	
Adjustable connector, horizontal	
Adjustable connector, vertical	
Rustproof steel, pickled	
Connection type	Screwless connector
Wide-span version	