


Technical data sheet

Cable ladder LCIS 60, 6 m C30

Item no. 6209636



Cable ladder with a 60 mm side height with welded C30 profile rungs which are open in an upwards direction. Rolled side rail for reinforcement and as edge protection. Fastening to the bracket takes place using clamping pieces, type LKS 40. The slot dimension of the rung is 16.5 mm and the appropriate clamp clip is type 2056.

Magnetic shield insulation without cover 10 dB, with cover 15 dB.




St Steel

FS Strip galvanised

Master data

Item no.	6209636
Type	LCIS 650 6 FS
Description 1	Cable ladder
Description 2	perforated rung, welded
Dimension	60x500x6000
Material	Steel
Material symbol	St
Surface	Strip galvanised
Surface to DIN	DIN EN 10346
Surface symbol	FS
Smallest sales unit (VG)	6 m
Weight	332,34 kg/100 m

Technical data



Length	6.000,00 mm
Width	500,00 mm
Height	60,00 mm
Side height	60,00 mm
Dimension B	500,00 mm
Rung version	Profile perforated
Side rail version	Flat profile
Fastening of rung	Welded
Suitable for maintaining electrical function	☐
Rail thickness	1,50 mm
Usable cross-section	20.000,00 mm ²
Usable cross-section	200,00 cm ²
Rustproof steel, pickled	☐
Side perforation	☒
Rung distance	300,00 mm
Wide-span version	☐

Technical data sheet

Cable ladder LCIS 60, 6 m C30

Item no. 6209636




Technical data

Appr. load:

Support spacing 1.5 m	3,30 kN/m
Support spacing 2.0 m	2,00 kN/m
Support spacing 2.5 m	1,30 kN/m
Support spacing 3.0 m	1,00 kN/m
Support spacing 3.5 m	0,78 kN/m
Support spacing 4.0 m	0,40 kN/m

Load diagram LCIS 60



1 Permitted cable tray/ladder load in kN/m without man load

2 Support width in m

3 Rail bend in mm at permitted kN/m

4 Load scheme during testing

— Load curve with cable tray/ladder width in mm

— Strut bend curve according to support width