

Technical data sheet

Cable tray MKS-Magic® 60, unperforated

Item no. 6059237



Unperforated cable tray with integrated quick fastening system. The usable length of the cable tray is 3,000 mm.

Continuous equipotential bonding is guaranteed without additional components.



St Steel

FS Strip galvanised

Master data

Item no.	6059237
Type	MKSMU 630 FS
Description 1	Cable tray MKSMU
Description 2	unperforated, quick connector
Manufacturer	OBO
Dimension	60x300x3050
Material	Steel
Material symbol	St
Surface	Strip galvanised
Surface to DIN	DIN EN 10346
Surface symbol	FS
Smallest sales unit (VG)	3 m
Weight	348,46 kg/100 m

Technical data

	Usable cross-section	17.800,00 mm ²
	Usable cross-section	178,00 cm ²
	Suitable for maintaining electrical function	☐
	Connector version	Integrated connector
	With cover	☐
	Mounting perforation in base	☐
	NATO hole pattern	☐
	Rustproof steel, pickled	☐
	Side perforation	☐
	Wide-span version	☐

Technical data sheet


Cable tray MKS-Magic® 60, unperforated

Item no. 6059237



Technical data

Dimensions




Length	3.050,00 mm
Width	300,00 mm
Height	60,00 mm
Side height	60,00 mm
Dimension B	300,00 mm
Plate thickness	1,00 mm

Appr. load:

Support spacing 1.5 m	1,50 kN/m
Support spacing 1.75 m	1,25 kN/m
Support spacing 2.0 m	1,00 kN/m
Support spacing 2.5 m	0,50 kN/m

Load diagram, cable tray, type MKSMU 60



- 1 Permitted cable tray/ladder load in kN/m without man load
- 2 Support width in m
- 3 Rail bend in mm at permitted kN/m
- 4 Load scheme during testing
- Load curve with cable tray/ladder width in mm
- Strut bend curve according to support width