

Technical data sheet

GESRM2 with protective frame - USB type

Item no. 7405595



Round installation unit with floor covering protection frame for direct installation in the connection socket UDL2-120 for indoor use. When closed, the installation unit can be wet-cleaned. The minimum installation depth is 70 mm. Cover plate and socket of the Modul 45 series should be ordered separately.





Zn Die-cast zinc

Chrome-plated

Master data

Item no.	7405595
Type	GESRC2
Description 1	Service outlet
Description 2	with prot. frame, Cr-plated
Dimension	130x130x64
Material	Die-cast zinc
Material symbol	Zn
Surface	Chrome-plated
Surface symbol	CR
Smallest sales unit (VG)	1 Piece
Weight	75,20 kg/100 pc.

Technical data



External diameter	130,00 mm
Floor covering protection frame	<input checked="" type="checkbox"/>
Floor care	Wet
Version for	Round
Suitable for wet care	<input checked="" type="checkbox"/>
Suitable for raised floor installation	<input type="checkbox"/>
Suitable for cavity floor installation	<input type="checkbox"/>
Suitable for underfloor ducts	<input checked="" type="checkbox"/>
With floor covering recess	<input type="checkbox"/>
Opening mechanism	Locking slider
Protection rating (IP) when unused	IP45