

Technical data sheet

UDHOME2 floor socket, with floor covering recess in stainless steel cover, equipped
Item no. 7368392



Square installation unit for use in dry-care cavity and screed floors in indoor areas. With recess in the hinged lid for the floor covering. Installation housing with pre-marked insertion openings for pipes (M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 85 mm, the height adjustment range +20 mm.

The scope of delivery contains one BS socket with switch and a mounting support for up to two LJ6C data modules.

Surfaces visible in the floor covering made of brushed stainless steel. The load-bearing capacity of 15 kN is only guaranteed when in an unused state.





VA Stainless steel, rustproof 1.4301

Brushed and laminated

Master data

Item no.	7368392
Type	UDHOME2 V BS
Description 1	Floor socket, complete
Description 2	with BS socket
Dimension	125x125x85
Material	Stainless steel, material no. 1.4301
Material symbol	A2
Surface	Brushed and laminated
Surface symbol	GUF
Smallest sales unit (VG)	1 Piece
Weight	210,00 kg/100 pc.

Technical data



Dimension h	85,00 mm
Wide external dimensions	125,00 mm
Wide installation dimensions	125,00 mm
Length of external dimensions	125,00 mm
Length of installation dimensions	125,00 mm
Number of mounting boxes	2
Cable outlet version	Swivellable cord outlet
Floor covering thickness	15,00 mm
Floor covering protection frame	<input type="checkbox"/>
Floor care	Dry
Version for	Square
Installation depth	110,00 mm
Floor height	85-105 mm
Suitable for wet care	<input type="checkbox"/>
Suitable for raised floor installation	<input type="checkbox"/>
Suitable for cavity floor installation	<input checked="" type="checkbox"/>
Suitable for underfloor ducts	<input checked="" type="checkbox"/>

Technical data sheet

UDHOME2 floor socket, with floor covering recess in
stainless steel cover, equipped
Item no. 7368392



Technical data

With floor covering recess	<input checked="" type="checkbox"/>
Height-adjustment range	85,00 - 105,00 mm
Opening mechanism	Tool