

Technical data sheet

Quick clip

Item no. 2149028



OBO Quick clip, type 2955/...: For all metric steel armoured pipes, as well as light-duty and heavy-duty metric insulation pipes. Suitable for mounting the OBO Quick pipe.

Pipe centring aids allow optimal attachment of the pipe and automatically turn the clip into the correct position.

Universal fastening option; can be arranged with the OBO Multi-quick and starQuick clip.

Slot for side alignment during mounting with wood screw or knock-in anchor.

Size M16-M32 can be screwed onto an M6 thread.

Recommended fastening spacing 50–60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.




PP Polypropylene

Master data

Item no.	2149028
Type	2955 M40
Description 1	Quick clip
Dimension	M40
Colour	Light grey
RAL number	7035
Material	Polypropylene
Material symbol	PP
Smallest sales unit (VG)	50 Piece
Weight	0,84 kg/100 pc.

Technical data



Dimension A	57,30 mm
Dimension B	16,00 mm
Dimension C	26 mm
Dimension D	39,20 mm
Dimension E	11,00 mm
Dimension F	4,60 mm
Dimension H	51,00 mm
Dimension h	12,00 mm
Expandable	<input checked="" type="checkbox"/>
Number of cables/pipes	1
Pull-out value	140 N
Fastening type	Screw hole
Breaking load	0,14 kN
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Closed	<input type="checkbox"/>
Nominal size	M40
Halogen-free	<input checked="" type="checkbox"/>
With inlay	<input type="checkbox"/>
Clip mounting	Gland hole, adjustable to fit thread M6
Clamping range D	40,00 - 40,00 mm
UV-resistant	<input type="checkbox"/>