

Technical data sheet

Aquasit cold casting compound, mixing bag

Item no. 2363002



Aquasit is a two-component casting compound for junction boxes in areas with continuous and extremely high levels of moisture. It can also be used against mechanical shock and vibrations.

At room temperature and when stored properly, the unopened aluminium bag can be used for up to 18 months. When the bags are mixed, the material should be used within 20 minutes. Practical experience, tests and approvals only apply in conjunction with OBO junction boxes.

Aquasit properties:

Protection rating with appropriate junction box: IP68 at 1.8 bar/1000 hrs

Rated voltage: 400 V

Penetration resistance: >20 kv/mm to VDE 0291 Part 2

Operating temperature: -40 to +90 °C

Processing temperature: 0 to +40 °C

Halogen-free, silicon-free, isocyanate-free

Environmentally friendly and without the need to be labelled



Master data

Item no.	2363002
Type	KVMM 1600
Description 1	Aquasit
Description 2	cast.compound for junct. boxes
Dimension	1600ml
Smallest sales unit (VG)	1 Piece
Weight	175,00 kg/100 pc.

Technical data

Length	680,00 mm
Width	175,00 mm
Height	15,00 mm
Contents	1.600,00 ml
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without