Technical data sheet

Aquasit cold casting compound, mixing bag

Item no. 2363008





Aquasit is a two-component casting compound for junction boxes in areas with continuous and extremely high levels of moisture. It can also be used against mechanical shock and vibrations.

At room temperature and when stored properly, the unopened aluminium bag can be used for up to 18 months. When the bags are mixed, the material should be used within 20 minutes. Practical experience, tests and approvals only apply in conjunction with OBO junction boxes.

Aquasit properties: Protection rating with appropriate junction box: IP68 at 1.8 bar/1000 hrs Rated voltage: 400 V Penetration resistance: >20 kv/mm to VDE 0291 Part 2 Operating temperature: -40 to +90 °C Processing temperature: 0 to +40 °C Halogen-free, silicon-free, isocyanate-free Environmentally friendly and without the need to be labelled

CE	IP 68	400 V	Fluor
----	----------	----------	-------

Master data		
Item no	Э.	2363008
Туре		KVMM 400
Descrip	ption 1	Aquasit
Descrip	ption 2	cast.compound for junct. boxes
Dimens	sion	400ml
Smalles	st sales unit (VG)	1 Piece
Weight	t	49,80 kg/100 pc.
Technical data		
Length	1	460,00 mm
Length Width		460,00 mm 140,00 mm
Width		140,00 mm
Width Height	its	140,00 mm 15,00 mm
Width Height Content For Ex z	its zone	140,00 mm 15,00 mm 400,00 ml