

# Technical data sheet

## Stainless steel pipe, V2A

Item no. 2046726



Electrical installation pipe without threaded ends to EN 61386-1 for mechanical protection of cables. With burr-free inner wall. Corrosion protection class 4 (high). Classification according to DIN EN 61386-1: 555711404010




**A2** Stainless steel, rustproof 1.4301  
**2B** Bright, reworked

### Master data

|                          |                                      |
|--------------------------|--------------------------------------|
| Item no.                 | 2046726                              |
| Type                     | S63W A2                              |
| Description 1            | Stainless steel pipe                 |
| Description 2            | without thread                       |
| Dimension                | ø63, 3000mm                          |
| Material                 | Stainless steel, material no. 1.4301 |
| Material symbol          | A2                                   |
| Surface                  | Bright, reworked                     |
| Surface symbol           | 2B                                   |
| Smallest sales unit (VG) | 9 m                                  |
| Weight                   | 227,50 kg/100 m                      |

### Technical data



|  |                                     |
|--|-------------------------------------|
| Length   | 3.000,00 mm                         |
| Dimension D                                    | 63,00 mm                            |
| Dimension L                                    | 3.000,00 mm                         |
| Dimension M                                    | M63                                 |
| Dimension t                                    | 1,50 mm                             |
| Surface-mounted                                | <input checked="" type="checkbox"/> |
| Pipe version                                   | Rigid without thread                |
| Concrete installation                          | <input checked="" type="checkbox"/> |
| Pressure resistance class                      | Very heavy (Class 5)                |
| Cavity wall installation                       | <input checked="" type="checkbox"/> |
| Installation on wood                           | <input checked="" type="checkbox"/> |
| Installation under the ground                  | <input checked="" type="checkbox"/> |
| Installation outdoors                          | <input checked="" type="checkbox"/> |
| Machines and system installation               | <input checked="" type="checkbox"/> |
| With sleeve                                    | <input type="checkbox"/>            |
| Polished surface                               | <input type="checkbox"/>            |
| Brushed surface                                | <input checked="" type="checkbox"/> |
| max. permitted ambient temperature             | -45,00 - 400,00 °C                  |
| Underfloor installation (bitumen, hot asphalt) | <input checked="" type="checkbox"/> |
| Underfloor installation (screed)               | <input checked="" type="checkbox"/> |
| Concealed                                      | <input checked="" type="checkbox"/> |

# Technical data sheet

Stainless steel pipe, V2A

Item no. 2046726



## Technical data

### Classification for electrical pipe standards

|                     |       |
|---------------------|-------|
| Classification code | 55571 |
|---------------------|-------|