Technical data sheet

Hot-dip galvanised steel pipe, without thread

Item no. 2046599

Electrical installation pipe without threaded ends according to EN 61386-1 for mechanical protection of cables. With burr-free inner wall. Corrosion protection class 4 (high).

E30 E90 St

St	Steel
FT	Hot-dip galvanised

Master data

Item no.	2046599
Type	S63W FT
Description 1	Plug-in conduit
Description 2	without thread
Dimension	Ø63, 3000mm
Material	Steel
Material symbol	St
Surface	Hot-dip galvanised
Surface to DIN	DIN EN ISO 1461
Surface symbol	FT
Smallest sales unit (VG)	9 m
Weight	223,00 kg/100 m

Technical data



Length	3.000,00 mm
Dimension D	63,00 mm
Dimension L	3.000,00 mm
Dimension M	M63
Dimension t	1,20 mm
Surface-mounted	☑
Pipe version	Rigid without thread
Outer-Ø	63,00 mm
Concrete installation	☑
Pressure resistance class	Heavy (Class 4)
Size	63
Cavity wall installation	☑
Installation on wood	☑
Installation under the ground	☑
Installation outdoors	☑
Machines and system installation	☑
With sleeve	☐
Polished surface	☐
Brushed surface	☐
max. permitted ambient temperature	-45,00 - 400,00 °C
Underfloor installation (bitumen, hot asphalt)	☑

Technical data sheet

Hot-dip galvanised steel pipe, without thread

Item no. 2046599

Technical data	
Underfloor installation (screed)	☑
Concealed	☑

Classification for electrical pipe standards	
Classification code	44571