


# Technical data sheet

## Cap nut cable gland, metric thread, extra long, black

Item no. 2022997



The quickest and most convenient way of providing strain relief and tightness with cable glands on junction boxes and housings is with the tried-and-trusted V-TEC VM cable glands from OBO. A protection rating of IP68 is achieved through the integrated sealing lip and the special OBO slat technology. Strain relief and tightness have been tested to DIN EN 62444. The connection threads are metric. Once screwed in place, the installation is there forever, as the optimum thread adjustment with the right pitch ensures permanent resistance to shaking. Applications: From private housing with junction boxes up to industrial applications in the distributor cabinet. Temperature range: -20 °C to +65 °C.




PA Polyamide

### Master data

Item no.	2022997
Type	V-TEC VM LL63 SW
Description 1	Cable gland
Description 2	fully metric long 24mm
Dimension	M63
Colour	Black
Material	Polyamide
Material symbol	PA
Smallest sales unit (VG)	5 Piece
Weight	7,50 kg/100 pc.

### Technical data



Dimension E	75,00 mm
Dimension L min.	41,50 mm
Dimension L max.	60,30 mm
Dimension L1	24,00 mm
Dimension L2	9,00 mm
WAF	68,00 mm
Version	Straight
Type of seal	Sealing ring
Bend protection	<input type="checkbox"/>
Sealing range D	36,00 - 48,00 mm
explosion-proof	<input type="checkbox"/>
Flat cable threaded connection	<input type="checkbox"/>
For Ex zone	Without
For Ex zone gas	Without
For Ex zone dust	Without
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Thread	M63x1,5
Thread type	Metric
Thread length	24,00 mm
Thread increase	1,80 mm
Nominal thread size	63
Fibre-glass reinforced	<input type="checkbox"/>
Halogen-free	<input checked="" type="checkbox"/>

# Technical data sheet

Cap nut cable gland, metric thread, extra long, black

Item no. 2022997



## Technical data

Installation torque	12,00 Nm
Impact category	A
Strain relief category	4
Multiple sealing insert	<input type="checkbox"/>
With locknut	<input type="checkbox"/>
Impact-resistant	<input type="checkbox"/>
Hexagonal corner dimension	75,00 mm
Protection rating	IP68
Splittable gland	<input type="checkbox"/>
max. permitted ambient temperature	-20,00 - 65,00 °C
Strain relief option	<input checked="" type="checkbox"/>