


Technical data sheet

Junction box X 01

Item no. 2005140



Junction box for the connection of cables and lines indoors and in outdoor areas. Square design with knock-out entries. Suitable for wall and ceiling mounting with the option to fasten outside, inside or to mount via the corner domes. Particularly impact resistant with IK09. Cover with quick lock, sealable. Made from halogen-free and UV-resistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650 °C. Impact resistance IK09 according to DIN EN 50102. Protection rating IP67 according to DIN EN 60529.




PC Polycarbonate

Additional product text, instruction	The junction box is tested according to DIN EN 60670-1, VDE 0606-1:2014 (EN 60670-1:2005 + Cor.:2007 + Cor.:2010 + A1:2013) and DIN EN 60670-22, VDE 0606-22:2007 (EN 60670-22:2006).
Additional product text 1	The junction box fulfils the protection type test requirements to IP 67 according to DIN EN 60529, VDE0470-1:2014 (EN 60529/AC:2016).
Additional product text 2	The base is black and the cover is signal red with black fastening elements.

Master data

Item no.	2005140
Type	X01 SW-RO
Description 1	Junction box
Description 2	with red cover
Dimension	95x95x60
Colour	Black/red
Material	Polycarbonate
Material symbol	PC
Smallest sales unit (VG)	1 Piece
Weight	16,00 kg/100 pc.

Technical data



Length	95,00 mm
Width	95,00 mm
Height	60,00 mm
Clear internal dimensions	85x85x45 mm
Dimension LxWxH	95x95x60 mm
Expandable	☒
No. of entries	7
Type of entry	Cuttable stepped membrane
Type of housing penetration	Pre-marking
Measured insulation voltage Vi	750,00 V
Equipment	Without
Cover	Not transparent
Cover fastening	Screwed
Entries	7 x Ø20
Entry from rear	☐
Explosion-tested version	☐
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C
Shape	Square
Fibre-glass reinforced	☒

Technical data sheet

Junction box X 01

Item no. 2005140



Technical data

Halogen-free	☒
Max. conductor cross-section	1,50 mm ²
With screening	☐
With cover	☒
Installation type	On cable tray
Mounting type	Wall/ceiling mounting
Nominal cross section	0,80 - 1,50 mm ²
Nominal voltage	750,00 V
Protection rating	IP67
Protection rating	IP 67
Protection rating IK code	IK09
Sealable	☒
Impact-resistant	☒
max. permitted ambient temperature	-25,00 - 65,00 °C
Transparent lid	☐
Weatherproof	☒